



Novara

Artificial leather collection

Technical data sheet

GENERAL		
Composition surface		88%PVC
Composition back cloth		12%PL
Roll width		138cm
Roll length		30m
Weight (UNI EN ISO 12127)		670gr/m ²
Thickness		0.90mm
TESTS	METHOD	RESULT / U.M.
Colour fastness to light	UNI EN ISO 105 B02	>6
Martindale abrasion	UNI EN ISO 12947-2 (rubs)	>55.000
Anti-bacterial activity	UNI EN ISO 20743-8.2	pass
Conformity to REACH		pass
Burning behaviour	UNI EN ISO 1021 part 1+2 FR BS 5852 Crib 5 CL1/IM M2 TB117E FAR 25.853 app F to part 25	pass

GENERAL INFORMATION										
										
Fireproof	Easy upholstery	UV and low t* resistant	Long life	REACH compliant	Waterproof	Antibacterial	Abrasion resistant	Easy to clean		



Dijle 17/A
2800 Mechelen
TEL : 0032-15/40.90.60
www.buvetex.be

CLEANING INSTRUCTIONS

Easily cleanable. Wipe clean with a slightly wet cloth. Use water and neutral soap. Use stain remover suited for artificial leather or standard detergents and alcohol that is properly diluted.

REMARKS

INTENSIVE DOMESTIC AND CONTRACT USE

Slight color differences between production batches can occur.

The test results only apply to the samples tested.

Buvetex can't be kept liable for inappropriate use of the artificial leather.