

Cavaliere soft

Transport upholstery

Technical data sheet

TYPE	artificial leather
APPLICATION	trimming and panel lining material
DESIGN NAMES	-

GENERAL		
Composition surface		100%PVC
Lamination		3mm FR PES foam
Roll width		>137cm
Weight (UNI EN ISO 12127)		650gr/m ²
Thickness		1.30mm
TESTS	METHOD	RESULT / U.M.
Fastness to rubbing (dry/wet)	UNI EN ISO 11640 (note)	dry 5 / wet >=4-5
Elongation at break	UNI EN ISO 3376 (%)	40-70%
Colour fastness to light	UNI EN ISO 105 B02 (note)	>=5
Colour fastness to perspiration (acid/alkali)	UNI EN ISO 11641 (note)	4-5
Flexing endurance Bally Flex	UNI EN ISO 4818/92 (cycles)	+100.000
Resistance to blocking	UNI EN ISO BS 3424	no blocking
Martindale abrasion	UNI EN ISO 12947-2 (rubs)	>75.000
Burning and melting behavior	ECE 118 R03 annex 6+7+8	pass
REPELLENCY AND CLEANABILITY		
Antibacterial		pass
CLEANING INSTRUCTIONS		
Wipe clean with a slightly wet cloth. Use water and neutral soap. Use stain remover suited for artificial leather.		
BIOCOMPATIBILITY		
REACH & RoHS compliant		
SUSTAINABILITY		

Part of UN sustainability program. Use of rain water harvesting system in all manufacturing units. Curb of fossil fuel and energy consumption by implementation of new technologies such as solar energy. Waste heat and water recovery. Waste reduction, from the beginning of production process.



REMARKS

*** VERY INTENSIVE USE*** Slight color differences between production batches can occur.

The test results only apply to the samples tested.

Buvetex can't be kept liable for inappropriate use of the artificial leather.