






Nabucco

Transport upholstery

Technical data sheet

TYPE	microfiber fabric
APPLICATION	seat upholstery
DESIGN NAMES	-

GENERAL		
Composition	55% PL + 35% PU + 10% CO	
Roll width	>140cm	
Roll length	+/- 30m	
Weight (UNI EN ISO 12127)	640gr/m ² (+/-5%)	
TESTS	METHOD	RESULT / U.M.
Tensile strength	UNI EN ISO 13934-1 (N)	weft 415/warp 870
Slippage resistance	UNI EN ISO 13936-1 (N)	weft/warp >200
Detachment resistance to backing	UNI EN ISO 2411: 2001 (N)	weft/warp >25
Pilling	UNI EN ISO 12945-2 (note)	>4/5
Fastness to rubbing (dry/wet)	UNI EN ISO 105 X12 (note)	4/5
Colour fastness to light	UNI EN ISO 105 B02 (note)	>=6
Colour fastness to perspiration (acid/alkali)	UNI EN ISO 105 E04 (note)	>=4/5
Martindale abrasion	UNI EN ISO 12947-2 (rubs)	>=50.000
Burning and melting behavior	ECE 118 R03 annex 6+7+8	pass
REPELLENCY AND CLEANABILITY		
Easy Clean (after extra process)	pass	
CLEANING INSTRUCTIONS		
Vacuum regularly. Wipe clean with a damp cloth. An appropriate upholstery shampoo can be used.		
    		



Dijle 17/A
2800 Mechelen
TEL : 0032-15/40.90.60
www.buvetex.be

REMARKS

*** VERY INTENSIVE USE*** Slight color differences between production batches can occur.

The test results only apply to the samples tested.

Buvetex can't be kept liable for inappropriate use of the fabric.

